

ROHDE & SCHWARZ

Make ideas real



SIGNAL AND SPECTRUM ANALYZER PORTFOLIO

Product Flyer | Version 02.02



SIGNAL AND SPECTRUM ANALYZERS



	R&S®FSW	R&S®FSVA3000	R&S®FSV3000	R&S®PVT360A	R&S®FPS	R&S®FPL1000	R&S®FSH	R&S®FPH	R&S®ZVH	R&S®ZPH	R&S®FPC	R&S®FSC
	High-performance analyzer with widest analysis bandwidth available on the market	Signal and spectrum analyzer with excellent performance and high speed for lab and production applications	Signal and spectrum analyzer optimized for high speed in 5G production systems	Combined vector signal analyzer and generator in one box with two TRX channels	Fast and compact signal and spectrum analyzer with good performance in production and in monitoring systems	General purpose spectrum analyzer	Handheld combination analyzer with spectrum analyzer up to 20 GHz and two-port vector network analyzer up to 8 GHz	Handheld spectrum analyzer up to 44 GHz	Handheld cable and antenna analyzer up to 8 GHz with optional vector network analyzer and spectrum analyzer	Handheld cable and antenna analyzer up to 4 GHz with optional spectrum analyzer	Bench spectrum analyzer with vector network analyzer and signal generator up to 3 GHz	Compact and cost-effective spectrum analyzer
Performance	●●●●●	●●●●●	●●●●	●●●●	●●●●	●●●	●●	●	●●	●	●	●
Frequency models	2 Hz to 8/13.6/26.5/43.5/50/67/85 GHz	10 Hz to 4/7.5/13.6/30/44/50/54 GHz	10 Hz to 4/7.5/13.6/30/44/50 GHz	400 MHz to 6/8 GHz	10 Hz to 4/7/13.6/30/40 GHz	5 kHz to 3/7.5/14/26.5 GHz	9 kHz to 20 GHz (3.6/8/13.6/20 GHz models available)	5 kHz to 44 GHz (2/3/4/6/8/13.6/20/26.5/31/44 GHz models available)	100 kHz to 8 GHz (3.6/8 GHz models available)	5 kHz to 4 GHz (3/4 GHz models available)	5 kHz to 3 GHz (1/2/3 GHz models available)	9 kHz to 6 GHz (3/6 GHz models available)
Analysis bandwidth	8.3 GHz	1 GHz	200 MHz	500 MHz	160 MHz	40 MHz	–	–	–	–	–	–
Phase noise	< –136 dBc (1 Hz) (f = 1 GHz, 10 kHz offset)	< –127 dBc (1 Hz) (f = 1 GHz, 10 kHz offset)	< –117 dBc (1 Hz) (f = 1 GHz, 10 kHz offset)	–120dBc (1 Hz) (f = 1 GHz, 10 kHz offset)	< –106 dBc (1 Hz) (f = 500 MHz, 10 kHz offset)	< –105 dBc (1 Hz) (f = 1 GHz, 10 kHz offset)	–105 dBc (1 Hz) (f = 500 MHz, 30 kHz offset)	–95 dBc (1 Hz) (f = 500 MHz, 30 kHz offset)	–105 dBc (1 Hz) (f = 500 MHz, 30 kHz offset)	–95 dBc (1 Hz) (f = 500 MHz, 30 kHz offset)	–92 dBc (1 Hz) (f = 500 MHz, 30 kHz offset)	–95 dBc (1 Hz) (f = 500 MHz, 30 kHz offset)
DANL, at 1 GHz, preamplifier OFF	< –150 dBm	< –152 dBm	< –148 dBm	n.a.	< –150 dBm	< –149 dBm	–146 dBm	–146 dBm	–146 dBm	–146 dBm	–150 dBm	–146 dBm
DANL, at 1 GHz, preamplifier ON	< –166 dBm	< –164 dBm	< –162 dBm	< –161 dBm (1Hz, nominal)	< –160 dBm	< –163 dBm	–165 dBm	–163 dBm	–165 dBm	–163 dBm	–165 dBm	–165 dBm
TOI	> 20 dBm	> 17 dBm	> 15 dBm	> 19 dBm	> 13 dBm	> 17 dBm	+15 dBm	+10 dBm	+10 dBm	+10 dBm	+10 dBm	+15 dBm
Highlights	real time up to 800 MHz; signal analysis applications: noise, phase noise, cellular, wireless, analog demodulation, vector signal analyzer, pulse, transient, amplifier, DOCSIS, avionics, EMI, satellite	signal analysis applications: noise, phase noise, cellular, wireless, analog demodulation, vector signal analyzer, pulse, transients, amplifier	signal analysis applications: noise, phase noise, cellular, wireless, analog demodulation, vector signal analyzer, pulse, transients, amplifier	2 signal analyzers and 2 signal generators in one box, 16 switchable RF ports, 5G NR, LTE, Wi-Fi measurements, general purpose measurements, high measurement speed	signal analysis applications: noise, phase noise, cellular, wireless, analog demodulation, vector signal analyzer, pulse, amplifier	battery, tracking generator; signal analysis applications: noise, analog demodulation, vector signal analyzer, NB-IoT (with R&S®VSE), EMI	handheld combination analyzer: spectrum, full two-port vector network analyzer, power meter, cellular demodulation, interference hunting, EMI receiver mode, EMF measurement, vector voltmeter, pulse measurement	handheld spectrum analyzer: spectrum, power meter, interference hunting, EMI receiver mode, pulse measurement, field strength meter, modulation analyzer (AM/FM/ASK/FSK), up to 9 hours operating time	handheld combination analyzer: spectrum, cable and antenna, full two-port vector network analyzer, power meter, vector voltmeter	handheld combination analyzer: spectrum, cable and antenna, power meter, interference hunting, pulse analyzer, signal generator, modulation analyzer (AM/FM/ASK/FSK), built-in bias tee, extremely fast boot and measurement time	economy spectrum analyzer with value of three: spectrum analyzer, vector network analyzer, signal generator, EMI receiver mode, modulation analyzer (AM/FM/ASK/FSK)	compact spectrum analyzer with great RF performance, small form factor
Dimensions	462 mm x 240 mm x 504 mm (18.15 in x 9.44 in x 19.81 in)	462 mm x 197 mm x 417 mm (18.15 in x 7.76 in x 16.42 in)	462 mm x 197 mm x 417 mm (18.15 in x 7.76 in x 16.42 in)	465.1 mm x 106.5 mm x 555.5 mm (18.17 in x 4.20 in x 21.87 in)	461 mm x 107 mm x 551 mm (18.15 in x 4.21 in x 21.69 in)	408 mm x 186 mm x 235 mm (16.06 in x 7.32 in x 9.25 in)	194 mm x 300 mm x 144 mm (7.6 in x 11.8 in x 5.7 in)	202 mm x 294 mm x 76 mm (8.0 in x 11.6 in x 3 in)	194 mm x 300 mm x 144 mm (7.6 in x 11.8 in x 5.7 in)	202 mm x 294 mm x 76 mm (8.0 in x 11.6 in x 3 in)	396 mm x 178 mm x 147 mm (15.6 in x 7.0 in x 5.8 in)	233 mm x 158.1 mm x 350 mm (9.2 in x 6.2 in x 13.8 in)

Note: The specified data may require special models or options.

HANDHELD SELECTION GUIDE



Frequency selection guide

	R&S®ZPH	R&S®ZVH		R&S®FPH				R&S®FSH				
Minimum frequency												
CAT/VNA mode	2 MHz	100 kHz		–				300 kHz (model .24/.28), 100 kHz (model .23/.30)				
SA mode	5 kHz (model .12)	100 kHz		5 kHz				9 kHz				
Maximum frequency												
Model	.02/.12	.24	.28	.02	.06	.13/.23	.26/.36	.44/.54	.04/.14/.24	.08/.18/.28	.13/.23	.20/.30
2 GHz				●								
3 GHz	●			○								
3.6 GHz		●							●			
4 GHz	○			○								
6 GHz					●							
8 GHz			●		○					●	● (CAT/VNA)	● (CAT/VNA)
13.6 GHz						●					● (SA)	
20 GHz						○						● (SA)
26.5 GHz							●					
31 GHz							○					
44 GHz								●				

- standard
- with optional upgrade

Functionality selection guide

	R&S®ZPH, model .02	R&S®ZPH, model .12	R&S®ZVH	R&S®FPH	R&S®FSH
Cable and antenna measurement	●	●	●		● ¹⁾
Transmission/reflection VNA	● (S ₁₁ only)	● (S ₁₁ , S ₂₁)	●		● ¹⁾
Spectrum measurement		●	●	●	●
Digital (mobile) modulation					●
Interference hunting		●		●	●
Power measurement (built-in/with power sensor)	●	●	●	●	●
Pulse measurement	●	●	●	●	●
EMF measurements		●		●	●

- functionality available

¹⁾ Model dependent.

Rohde & Schwarz

The Rohde & Schwarz technology group is among the trailblazers when it comes to paving the way for a safer and connected world with its leading solutions in test & measurement, technology systems and networks & cybersecurity. Founded more than 85 years ago, the group is a reliable partner for industry and government customers around the globe. The independent company is headquartered in Munich, Germany and has an extensive sales and service network with locations in more than 70 countries.

www.rohde-schwarz.com

Service at Rohde & Schwarz You're in great hands

- ▶ Worldwide
- ▶ Local and personalized
- ▶ Customized and flexible
- ▶ Uncompromising quality
- ▶ Long-term dependability

Sustainable product design

- ▶ Environmental compatibility and eco-footprint
- ▶ Energy efficiency and low emissions
- ▶ Longevity and optimized total cost of ownership

Certified Quality Management

ISO 9001

Certified Environmental Management

ISO 14001

Rohde & Schwarz training

www.training.rohde-schwarz.com

Rohde & Schwarz customer support

www.rohde-schwarz.com/support

